DENSO

Leader in Advanced Technology

BHT-900 Series






BHT-900



BHT-900

- Linear scan engine
- Light weight and ergonomic
- USB connectivity
- Optional Bluetooth
- Alkaline or rechargeable battery
- BHT-8000 application support







Device type	BHT-904B Batch model	BHT-904BB Bluetooth model
Cradle I/F	RS-232C / USB	
Charger unit	1 slot unit charger / 4 slot unit charger	
Operating system	BHT-OS	
Scanning system	CCD	
Scanning width	40 mm	
Memory	RAM 2MB / Flash 16MB	
Reading confirmation	3-color LED (Blue/Red/Green) Speaker Vibration	
Display size	128 x 96 dot	
Display area	32.6 x 24.5 mm(1.6 inch)	
Display font	8 chars x 6 line (Standard font size) 10 chars x 8 line (Small font size)	
Display backlight	White	
Key number	28 keys(including side trigger key)	
Key trigger	3(Center key & Side trigger key x 2)	
Key layout	Mobile phone layout	
Communication I/F	- Bluetooth Ver 2.1+EDR(SSP, DUN) USB Ver 2.0 Max 480Mbps IrDA Ver 1.2 Max 460.8kbps	
Power	AA Dry cell Ni-MH battery	
Operation hours	Up to 200 hours	
Environment resistant	Drop resistance:1.2 m x 60 times IP54(Splash & Dust proof)	
Dimensions	149 51(40) 28(24) mm	
Weight	160g	

Specifications are subject to change without notice. (ver.1.0)
DENSO and the DENSO logo are registered trademarks of DENSO Corporation.
BHT and QR Code are registered trademarks of DENSO Wave Incorporated.