

Specifications

CLS-300

Printing Method	Direct Thermal Printing	
CPU	32bit RISC CPU	
Printing Speed (Max.)	up to 102 mm/sec (4 inches/sec)	
Fonts	1 Scalable, 8 Bitmap resident	
True type Download	Supported Standard	
Emulations (languages)	N/A (EPL specialized for graphic printing)	
Media Type	Roll or Fanfold; Continues or Perforated; die cut labels; Tags & Tickets	
Media Sensing	Fixed transmissive sensor, Reflective Sensor, central aligned	
Resolution/Dot pitch	203 dpi, 8 dots/mm	
Media width (Min-Max)	25.4 - 118 mm	1 - 4.65 inches
Media Roll Size (Max)	127 mm, 5 inches (Internal)	
Media Thickness (Min-Max)	0.06 - 0.20 mm	0.003 - 0.008 inches
Printing width (Max)	108 mm	4.25 inches
Standard Interface	USB	Full Speed USB1.1
Memory	SDRAM	16 Kb
	Flash Memory	64 Kb, 4 Kb available for user
Weight	2 Kg	
External Dimensions (W x D x H)	168 x 222 x 178 mm	
Operating temp. range	5 to 40 °C, Humidity 30 to 85%	
Storage temp. range	-20 to 50 °C, Humidity 10 to 90%	
Safety compliance	FCC : class A, CB, CCC, CE(EMC), UL, c-UL, C-Tick	