

Specifications - P25-M

Keypad	Power, Feed and Mode Buttons
Print Method	Direct thermal
Print Resolution	203 dpi horizontal & vertical
Graphic mode	384 dots wide (max), length unlimited
Character Sets	Latin alphabet: 12 x 24, 16 x 32 (Lucide font) Chinese character: 24 x 24, 32 x 32 Scalable up to 8 times original size
Bar Code	UPC-A, UPC-E, EAN-8, EAN-13, PDF417
Tear Bar	Embedded in printer mechanism
Mount	Rubber pads for desk mount Two threaded inserts for hard mount Optional mounting solutions available.
Regulatory Approvals	FCC, CE
Drop Specification	1 m (3.3') with soft skin case
Battery/Power	7.4v 1400mAH replaceable Lithium-ion battery, self discharge rate <10% week, AC charging adapter 100-240VAC, 50/60 Hz
Dimensions(W x D x H)	75 x 112 x 46 mm (3.0 x 4.4 x 1.8")
Weight	294g/104oz/0.65 lbs (paper and battery included)
Software/Development	Developer guide includes reference code for java, Window Mobile, and WinCE OS environments.
Environments	Operating temperature: -5 ~ 50°C (23 ~ 122°F) Operating humidity: 20 ~ 85% RH Storage temperature: -20 ~ 60°C (-4 ~ 140°F) Storage humidity: 5 ~ 90% RH
Magnetic-Stripe Reader	3 Track Support, Bi-directional
Security	3DES encryption, Master/Session and DUKPT key management