

Specifications	Dualys 3
Printing Method	Colour Dye sublimation and Monochrome thermal transfer
Printing Speed (Max.)	Colour (YMCKO) 1 side up to 150 cards/hour Colour (YMCKO) 2 sides up to 125 cards/hour Monochrome 1 side up to 1000 Cards/hour Monochrome 2 sides up to 350 Cards/hour
Resolution/Dot pitch	300 dpi, 11.8 dots/mm
Residential fonts	Arial 100, Arial Bold 100 Barcode: Code 39, Interleave 2 of 5
Software	Comes standard with eMedia Card Designer Software for designing and editing badges. Compatible with Windows? 7, XP, Vista & 2003 Server Connection to Microsoft? Excel databases
Supported OS Platforms	Windows? 7 (32 & 64 bits), XP, Vista (32 & 64 bits), Windows? 2003 Server. Windows? 2000 drivers available on request. MAC OS X v10.2 ~ 6 Linux
Media Type	All PVC, Composite PVC Cards, PET, ABS1 and special varnished (under specific conditions) cards
Card Format	ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 3.375? x 2.125?)
Card thickness	From 0.25 mm (10 mil) to 1 mm (40 mil) 0.25 cards should only be used for Monochrome printing
Card Feeder Capacity	100 cards (0.76 mm - 30 mil), 300 cards (0.25 mm - 10 mil)
Output hopper Capacity	100 cards (0.76 mm - 30 mil), 300 cards (0.25 mm - 10 mil)
Standard Interface	USB
Optional Interfaces	Ethernet LAN
Operator Panel	1-Button and 4-LED control Panel
Memory	16 Mb RAM
Weight	7.4 Kg
External Dimensions (W x D x H)	237 x 447 x 235 mm
Operating temp. range	15 to 30 ?C, Humidity 20 to 65% non condensing
Storage temp. range	-5 to 70 ?C, Humidity 20 to 70% non condensing
Operating ventilation	free air
Power Supply	220-240V, 1.8A, 50/60Hz Printer 24 Volts DC 3A
Warranty	Printer, Print Head: 3 Year Warranty, unlimited passes (subject to observance of specific conditions and use of Evolis genuine consumables)