

Specifications-MS1650B-R

Scan Pattern	Area Imager
Scan Rate	52 scan lines/sec
Scan Rate	52 scan lines/sec
Minimum Bar width	0.173 mm, 6.8 mil
Print Contrast	35% minimum reflectance difference
Depth of Field	0 - 254 mm for 13 mil bar-codes
Width of Field	49 x 19 mm @ 20 mm, 264 x 106 mm @ 280 mm
Decoding Capability	Auto-discriminates between following symbologies: All standard 1D, GS1 Databar™ & GS1 Databar™ expanded, PDF417, microPDF, Maxicode, Data Matrix, QR code, UCC, EAN composites, Postals and Aztec.
Beeper Operation	7 Tones or no Beep
Indicators (LED)	Blue = unit powered, ready to scan; White = good read
	RS-232
	IBM 46xx
System interfaces available	Keyboard Wedge
	Stand alone Keyboard
	USB
Height x Width x Depth	62 x 80 x 116 mm
Weight	204 g
Input Voltage	5 VDC $\pm$ 0.25 V
Power	1.65 W Typical, standby 800 mW
	Operating: 330 mA Typical @ 5 VDC
Current	Standby Current: 160 mA Typical @ 5 VDC
	Class 1: IEC60825-1: 1993/A1: 1997 +A2:2001
LED Class	
	Class 1: IEC60825-1: 1994/A11: 1996 +A2:2001
EMC	FCC Class A IEC60825-1 LED Safety
ESD Protection	Functional after 100 15kV discharges