

Specifications- IT1200G

Scan pattern	Single Line
Scan Rate	100 scans/sec
Scan Angle	Horizontal 30°
Pitch, Skew	60°, 60° 40 to 129 mm on 5 mils barcode 27 to 185 mm on 7.5 mils barcode
Depth of field	0 to 221 mm on 10 mils barcode 0 to 254 mm on 13 mils barcode 0 to 281 mm on 20 mils barcode
Print Contrast	10% minimum reflectance difference
Decoding Capability	Decodes all standard 1D, and GS1 Databar Symbologies Multi Interface RS232 (TTL +5V, 4 signals)
Communications	KBW USB (HID Keyboard, Serial, IBM OEM) RS232C (+/- 12V) IBM RS485 supported through adapter cable
Shock	Normal operation after 30 drops to concrete from 1.5 m
Sealing	IP42
Light Levels	0 ~ 70,000 lux
Dimensions LxWxH	66 x 180 x 97 mm
Weight	125 g
Input Voltage	5V +/- 5%
Operating Power	700 mW; 140 mA (typical) @ 5V
Standby Power	350 mW; 70 mA (typical) @ 5V
Operating Temperature	0°C ~ 50°C
Humidity	0% ~ 95% Non Condensing
Warranty	5 Year Limited Factory Warranty (not on Cable)