

## HM518 Rugged Tablet POS System

### Introducing the Hisense HM518 Rugged Tablet POS System!



#### Rugged and lightweight Point-of-Sale (POS) system for harsh environments

Run your retail or hospitality business more efficiently with a stylish, reliable and space-saving **Hisense HM518 Rugged Tablet POS**. It has a Windows® operating system and is equipped with an optional, built-in Magnetic Stripe Reader (MSR), Near Field Communication (NFC) & Smart Card reader.

The 10.1 inch, bezel-free and wide screen display provides an optimal viewing experience so that you won't miss a beat while doing business. The display is also designed with Projected Capacitive (PCAP) touch technology that helps to extend the operating life and allow multi-touch gesture control. You can also use the wide range of ports to connect peripheral devices in the docking station.

If performance is a concern for you, then the **Hisense HM518 Rugged Tablet POS** is a must-have for your business. It's also faster and easier to update than a fixed-line (traditional) POS.

### Key Features and Benefits

- Bezel-free, flat and PCAP multi-touch 10.1" wide screen display that optimizes viewing
- Ergonomic design with hand strap
- Lightweight and rugged design that passed a 1.2 meter (4 feet) drop test
- IP54 grade that maximizes the physical durability of the front panel
- Optional Barcode Reader, 3G, GPS function
- Removable battery to support long hours of operation
- Docking station with input/output ports to connect various peripheral devices that match industry requirements

### Product Specifications

Model Name	HM518
Processor	Intel Celeron Processor N2807 1.58GHz
Memory	
Storage	64GB eMMC
Panel	10.1" TFT LCD (LED back light) / resolution 1280 x 800
Touch layer	True flat-projected capacitive technology(10 points)

<b>Camera</b>	5MP AF rear-facing camera (supports 2D barcode function)
<b>Integrate card reader</b>	3 tracks MSR
	Smart Card Reader
	NFC (Supports MIFARE one and MIFARE CPU card)
<b>Wireless connection</b>	Wi-Fi® 802.11a/b/g/n/ac 2.4GHz/5GHz & BT 4.1
<b>Speaker</b>	8Ω, 1W
<b>Microphone</b>	Support
<b>G-sensor</b>	Support
<b>Audio</b>	3.5mm socket(nokia)
<b>I/O interface</b>	Micro-SD, USB 2.0, DC Jack, Audio(nokia)
<b>Buttons</b>	Power, 1D barcode scanner
<b>Indicator light</b>	1 for power; 1 for 3G status; 1 for card reader
<b>Battery</b>	4000mAh (7.4V)
<b>Dock station I/O ports</b>	3 USB 2.0
	One 100M LAN
	1 RJ11(12V/24V option) for Cash drawer(default 24V)
	COM1,COM2 (non-standard, refer to manual)
	1 VGA for second display
<b>Optional items</b>	Scanner ( 1D barcode )
	3G (WCDMA frequency with 900/2100MHz, 850/1900MHz option); GSM/GPRS/EDGE: frequency with 900/1800MHz, 850/1900MHz option
	GPS
<b>Power adapter</b>	12V 40W
<b>EMC and Safety</b>	FCC class-B,CE class-B, RoHS
<b>Operating Environment</b>	0°C ~ 40°C (32°F~104°F) / 20% ~ 80% RH non-condensing
<b>Storage Environment</b>	-20°C ~ 60°C(-4°F~140°F) / 10% ~ 90% RH non-condensing
<b>Color</b>	Black
<b>Tablet Dimension (L x W x H )</b>	270mm x 195mm x16.8mm(10.63" x 7.67" x 0.66")
<b>Drop test</b>	4 feet
<b>Weight (tablet only)</b>	1.0kg (2.2 lbs)
<b>Operating System (OS) supported</b>	Windows 8.1 / Windows 10

**Disclaimer:** This product specification is subject to change without prior notice. In addition, images shown throughout this brochure are for illustrative purposes only and may differ from the actual product.

CE FC RoHS