

SAMSUNG mini printers



SRP-370/372



Samsung Mini Printers keep at the forefront of technology and commitment to reliability with new model. The **SRP-370** two color fast print speed thermal printer is ideal for retail and hospitality applications and allows you to print receipt with company logos and barcodes plus add coupons. In addition, **SRP-372** high density(203dpi) version is also available.



- POS system
- Kitchen printer
- Electronic scale
- EFT-POS
- Measuring equipment
- Lottery

Versatile POS printer features for all Retail and Hospitality solutions!!!

• The fastest speed in its class

Printing at maximum speed of 200mm/sec, The SRP-370 is one of the fastest printers – even when it prints barcodes and logos.

• Various paper roll sizes

You can select the paper width only with the paper guide. The standard width 80mm roll is ideal for POS receipts, especially when used to provide promotional coupons and vouchers. For other uses like back of house information printing the 82.5mm or 58mm roll may be more than adequate. And also capable of handling paper rolls of up to 105 mm in diameter, the compact SRP-370 can be unobtrusively located in any retail environment.

• Easy System Integration

With fast moving technology in IT solution it is important to have simple integration of peripheral devices. The SRP-370 is no exception, drivers are available for Windows 95/98/ME/NT4.0/XP /2003 server and OPOS.

• Drop In and Print Paper Loading

A simple drop-in loading system means that even inexperienced operators can load paper rolls with the minimum of effort.

• Satisfy with multiple interfaces


The SRP-370 has versatile, interchangeable interfaces such as Serial, Parallel, USB, Ethernet and Bluetooth options with new technology interfaces POWRED USB Y-cable and USB+SERIAL interface. If you want to connect to low cost cash registers or the most sophisticated EPOS system or hospitality management system just choose the interface that your system needs.

• Software utilities

Logo/firmware download program helps you use logo efficiently and easily. Also available is the Store Maker logo download utility allowing updates of logos and coupons.



Samsung Mini Printers keep at the forefront of technology and commitment to reliability with new model. Two color thermal printing capability makes it ideal for corporate branding, highlighting specials, coupons, customer loyalty and restaurant applications.



✓ Feeding line count✓ Cutting count



AUTO CUTTER

• Customizing your Receipt

By utilizing the statistic memory of the SRP-370 you can provide unique identity to your receipts.

Recommend you to monitor the life span of key components by statistic data saving. It's very easy to select the printer settings by virtual memory switch.

• The powerful features for Kitchen printer

The splash proof cover, wall mount bracket and internal/external buzzer is fitted in food and beverage preparation areas as standard equipment. The SRP-370 has these powerful features to make all users satisfy in the busy and flurried environment.















SPECIFICATION FOR THE SRP-370/372 THERMAL PRINTER

PRINT	PRINT METHOD	Direct Thermal
	PRINT SPEED	200 mm/ sec (61.7 LPS)
	PAPER SUPPLY METHOD	Easy Paper Loading
	RESOLUTION	180 dpi (7dot/mm) * SRP-372 : 203 dpi(8dot/mm)
	CHARACTER SET	Alphanumeric Character: 96
		Extended Graphic: 128 X 7 page (1space page)
		International Character: 32
	CHARACTER SIZE	Font A: 12 X 24, Font B: 9 X 17
	CHARACTER PER LINE	Font A: 42, Font B: 56
	PAPER TYPE	Mono & 2 color thermal paper
PAPER ROLL	WIDTH	57.5 mm \pm 0.5 mm, 79.5 mm \pm 05. mm, 82.5 mm \pm 05. mm
	DIAMETER	Max.Ø 105.0 mm
RELIABILITY	MCBF	70,000,000 Lines
RELIABILITY	AUTO CUTTER	1 million cuts
	TPH	150,000,000 up to pulse 150Km)
BARCODES		1D : EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Code Bar, UPC-A, UPC-E / 2D (Option): PDF417, QR Code
EMULATION		ESC/POS
FLASH MEMORY		16 Mbit
DATA BUFFER		64 Kbit
DRIVER		Windows95/98/Me/2000/NT/XP/2003 server, USB, OPOS
SENSOR		Paper Near End Sensor, Paper End Sensor
DRAWER PORT		2 Port
CONNECTIVITY	INTERFACE	RS-232C, IEEE1284,USB,RS-485,Ethernet,Bluetooth
OPTIONS	LANGUAGE	Buyer language support
	WALL MOUNT	RWM-350
DOWED	CLIDDLY	
POWER	SUPPLY	AC120V~230V±10%(Include), DC24V, 2.3A
DIMENSION		146(W) X 204(L) X 160(H) mm
OPERATING TEMP.		0. 45%
OI ERAIING IEMP.		0 ~ 45°C

Guillotine (1,000,000 Cuts)